## KERN RFE6K3M



Compact portion scale with 2 XXL displays â weight, unit price, total price and TARE value at a glance



| Measuring system                                |                      |
|---|----------------------|
| Adjustment options:                             | External calibration |
| Linearity:                                      | 3 g   6 g            |
| Number of weighing ranges:                      | 2                    |
| Readability [d]:                                | 1 g   2 g            |
| Recommended adjusting weight:                   | 6 kg (M1)            |
| Repeatability:                                  | 1 g   2 g            |
| Resolution:                                     | 3 3.000              |
| Resolution (non verifiable):                    | 6000                 |
| Resolution (verifiable):                        | 6000                 |
| Stabilisation time under laboratory conditions: | 2 s                  |
| Tare range:                                     | -5,998 kg            |
| Warm up time:                                   | 10 min   10 min      |
| Weighing capacity [Max]:                        | 3 kg   6 kg          |
| Weighing system:                                | Strain gauge         |
| Weighing units:                                 | kg g                 |

| Display                      |      |  |
|------------------------------|------|--|
| Additional Display possible: | no   |  |
| Display digit height:        | 2 cm |  |

| Technical data about verification               |         |  |
|---|---------|--|
| Minimum load [Min]:                             | 20 g    |  |
| Periodic Verification for Italy:                | 969-112 |  |
| Verification approval conforming to 2014/31/EU: | yes     |  |
| Verification by KERN possible:                  | yes     |  |
| Verification class:                             | III     |  |
| Verification value [e]:                         | 1g 2g   |  |

|   | ur | 0  | ч | $\sim$ | n | 0 |
|---|----|----|---|--------|---|---|
| ш | uı | ΙU | ш | U      | ш | 5 |

PRE-TARE function: yes

| Environmental conditions       |        |
|--------------------------------|--------|
| Maximum humidity:              | 80 %   |
| Maximum operating temperature: | 40 °C  |
| Minimum ambient temperature:   | -10 °C |
| Minimum humidity:              | 0 %    |

| Power supply                    |                         |
|---------------------------------|-------------------------|
| Battery:                        | no battery              |
| Charging time:                  | 12 h                    |
| Input voltage:                  | 220 V - 240 V AC 50 Hz  |
| Mains adapter:                  | Mains adapter external  |
| Mains adapter/adapter included: | UK US EURO CH           |
| Operating time (Backlight off): | 60 h                    |
| Operating time (Backlight on):  | 30 h                    |
| Rechargeable battery:           | Rchrg. battery optional |

| OCI VICC                   |                             |  |
|----------------------------|-----------------------------|--|
| Adjustment at the location | on of installation: 961-248 |  |
| DAkkS Certificate:         | 963-128                     |  |
| Verification:              | 965-228                     |  |

| Satisgory      |                       |
|----------------|-----------------------|
| Brand:         | KERN                  |
| Category:      | Balances              |
| Product Group: | Price computing scale |

| Packaging & shipping          |                    |
|-------------------------------|--------------------|
| Delivery:                     | 24 h               |
| Dimensions packaging (WxDxH): | 530 x 380 x 210 mm |
| Gross weight:                 | 5,500 kg           |
| Net weight:                   | 4,200 kg           |
| Shipping method:              | Parcel service     |

| Construction                          |                    |
|---------------------------------------|--------------------|
| Casing material:                      | Plastic            |
| Dimensions housing (WxDxH):           | 320 x 450 x 130 mm |
| Dimensions of display device (WxDxH): | 320 x 130 x 80 mm  |
| of stand:                             | 39,500 cm          |
| Level indicator:                      | yes                |
| Material weighing plate:              | stainless steel    |
| Overall dimensions mounted (WxDxH):   | 320 x 450 x 410 mm |
| Revolving screw feet:                 | yes                |
| Weighing surface (WxD):               | 230 x 300 mm       |

## KERN RFE6K3M



Compact portion scale with 2 XXL displays â weight, unit price, total price and TARE value at a glance

## Piktogramme STANDARD Lalext Memory RS 232 UNIT MULTI DMS 1 DAY OPTION DAkks ACCU +3 DAYS FACTORY